







Hybride Mittelstücke

	Typ	Dämpfung	
		Multimode PC	Singlemode PC & APC
	E-2000 / DIN	$\leq 0.15 \pm 0.1$ dB	$\leq 0.2 \pm 0.1$ dB
	E-2000 / FC	$\leq 0.15 \pm 0.1$ dB	$\leq 0.2 \pm 0.1$ dB
	E-2000 / SC	$\leq 0.15 \pm 0.1$ dB	$\leq 0.2 \pm 0.1$ dB
	E-2000 / ST	$\leq 0.15 \pm 0.1$ dB	$\leq 0.2 \pm 0.1$ dB
	F-3000 / DIN	$\leq 0.2 \pm 0.1$ dB	$\leq 0.4 \pm 0.2$ dB
	F-3000 / E-2000	$\leq 0.2 \pm 0.1$ dB	$\leq 0.4 \pm 0.2$ dB
	F-3000 / FC	$\leq 0.2 \pm 0.1$ dB	$\leq 0.4 \pm 0.2$ dB
	F-3000 / SC	$\leq 0.2 \pm 0.1$ dB	$\leq 0.4 \pm 0.2$ dB

Hybride Mittelstücke

	SC-ST Simplex	$\leq 0.15 \pm 0.1 \text{ dB}$	$\leq 0.1 \pm 0.1 \text{ dB}$ (nur PC)
	SC-ST Duplex	$\leq 0.15 \pm 0.1 \text{ dB}$	$\leq 0.1 \pm 0.1 \text{ dB}$ (nur PC)
	LC-SC Simplex		$\leq 0.3 \pm 0.1 \text{ dB}$ (nur PC)

Material Zentrierhülse ZrO₂, geschlitzt